



STAS PICTURE HANGING SYSTEMS ESP 245 5633 AD EINDHOVEN THE NETHERLANDS P.O. BOX 1049 5602 BA EINDHOVEN THE NETHERLANDS
TELEPHONE +31 (0)40 2924848 FAX +31 (0)40 2924849 INFO@STAS.NL WWW.STAS.NL ING-BANK ACCOUNT NO. 68.40.82.233
IBAN CODE. NL38INGB0684082233 SWIFT INGBNL2A VAT NO. NL809287766B01 CHAMBER OF COMMERCE EINDHOVEN NO. 171.27.229

DECLARATION OF THE PRODUCER

1.Producer of the product

STAS picture hanging systems B.V.
Esp 245
5633 AD Eindhoven
The Netherlands
T +31 (0) 40-292 48 48
F +31 (0) 40-292 48 49
E sales@stas.nl
W www.stas.nl

2.Name of the product:

STAS U-railmulti System /article code VP10200/VP10300/VP20200/VP30200/VP30300

3.Statistical classification of produkt:

Aluminium bars, rods and profiles: 76042100

4.The purpose and domain

The STAS u-railmulti has been purpose-designed to turn your suspended ceiling into a flexible hanging system in a matter of minutes. The rail is available in the same colour as the wooden tile support strip and attaches almost completely invisibly to the ceiling tile support strips.

In rooms where a suspended ceiling has been installed, the STAS u-railmulti is not only the perfect hanging solution for works of art, it can also be used to hang notice boards and whiteboards.

5.Technical specification

- aluminium rail
- dimensions 17 x 14mm
- capable of carrying loads up to 30 kg per meter
- available in white, black or a natural aluminium colour to suit your ceiling supports

Further specifications are in enclosed technical document: [stas_u-railmulti_en.pdf](#)



Art Jewels Made by Stas



STAS PICTURE HANGING SYSTEMS ESP 245 5633 AD EINDHOVEN THE NETHERLANDS P.O. BOX 1049 5602 BA EINDHOVEN THE NETHERLANDS
TELEPHONE +31 (0)40 2924848 FAX +31 (0)40 2924849 INFO@STAS.NL WWW.STAS.NL ING-BANK ACCOUNT NO. 68.40.82.233
IBAN CODE. NL38INGB0684082233 SWIFT INGBNL2A VAT NO. NL809287766B01 CHAMBER OF COMMERCE EINDHOVEN NO. 171.27.229

6. The above system is not being classified as the building production.

Carrying capacity up to 30 kg/m¹, determined on the base of STAS long-term stress testing procedure. The stress testing has been done for use within normal parameters, as with 8 screws per m¹ and use inside buildings.

Summary:

STAS declares with the full liability that the product is matching the technical specifications indicated in points. The present document is not a declaration of the agreement in understanding regulations of the certification CE and CoD.

STAS picture hanging systems

Paul van Summeren

Art Jewels Made by Stas

